










YEAR



Dimensions



Specifi

IMAGE

Image sensor

Total pixels



IIICatio	ons	C QL) US LISTED
r	5MP 1/2.8" CMOS	
	2592 (H) X 1944 (V)	
	0.13 lux (color)	

Summary

5мР

Resolution

This MEGApix® IVA™ IP camera is your gateway to powerful video analytics features. It is NDAA compliant and provides 5MP resolution at real-time 30fps. The MEGApix IVA cameras have a powerful engine to detect and classify people and vehicles in real-time. IVA+ license upgrade offers advanced Video Content Analysis detection capabilities. This camera features Star-Light Plus™ color in near-total darkness technology for quality video in any lighting condition, simultaneous H.265/H.264/MJPEG codec support and a 2.8mm fixed lens. The weather-resistant vandal ball cameras are IP67-rated and offer true 90° tilting and 360° rotation, eliminate IR reflections and offer easy angle adjustment to pan, rotate and tilt the camera for optimal image quality. All MEGApix® cameras are ONVIF conformant, assuring their successful integration with any open platform solution on the market.

2.8mm Fixed Lens

Features

- 5MP 1/2.8" image sensor at real-time 30fps
- Star-Light Plus™ color in near-total darkness technology
- Intelligent Video Analytics (IVA)
- Extended Intelligent Video Analytics (IVA+ license required)
- Seamless integration and control of IVA rules with DW Spectrum® IPVMS
- Reduce false alarms
- Increase your recording storage with logic rules and smart recording
- 2.8mm fixed lens
- True Wide Dynamic Range (WDR)
- Triple codecs (H.265, H.264, MJPEG) with simultaneous streaming
- 100' Smart IR™ with intelligent camera sync
- Vandal ball housing reduces IR reflection with true 90° tilting and 360° rotation
- Smart DNR™ 3D digital noise reduction
- True day/night mechanical IR cut filter
- Programmable privacy zones
- Auto gain control (AGC)
- Auto white balance (AWB)
- Motion detection
- PoE class 3 and DC12V
- **UL** listed
- NDAA compliant
- IP67 dust-tight and waterproof to 3 feet
- IK 10-rated impact-resistant
- 5 year warranty



Accessories (Optional)





Junction box





Minimum scene illumination 0.0 lux (B/W) LENS Focal length 2.8mm, F1.8 Lens type Fixed lens HFOV / VFOV 103° / 78° IR distance 100ft range **OPERATIONAL** IVA license: intrusion, line crossing, counting line, loitering, enter, exit, tamper Intelligent Video Analytics IVA+ license: object removed, tailgating, direction, stopped, appear, disappear, object left Shutter mode Auto, manual, anti-flicker, slow shutter Shutter speed 1/15 ~ 1/32000 1/2, 1/3, 1/5, 1/6, 1/7.5, 1/10 Slow shutter Auto gain control Day and night Auto, day (color), night (B/W) Smart DNR™ 3D Digital noise reduction 3D-DNR Wide Dynamic Range True WDR, 120dB (WDR) Privacy zone 16 programmable privacy masks Backlight compensation Yes (BLC) Mirror and flip Alarm notifications Notifications via e-mail and FTP server recording **NETWORK** RJ45 (10/100Base-T) LAN Video Compression type H.265, H.264, MJPEG H.265: 2592x1944, 2304x1296, 2.1MP/1080p, 720p, VGA, D1, CIF H.264: 2592x1944, 2304x1296, 2.1MP/1080p, 720p, VGA, D1, CIF MJPEG: 2.1MP/1080p, 720p, 800x600, VGA, 768x432, D1, CIF Resolution Up to 30fps at all resolutions Frame rate H.265 / H.264: 32Kbps ~ 14Mbps Video bitrate MJPEG: 1Mbps ~ 40Mbps Bitrate control H.265 dual-stream or simultaneous H.265 / H.264 / MJPEG Streaming capability Dual-stream at different rates and resolutions IPv4. IPv6 TCP/IP, UDP, AutoIP, RTP (UDP/TCP), RTSP, NTP, HTTP, HTTPS, SSL, DNS, DDNS, DHCP, FTP, SMTP, ICMP, SNMPv1/v2/v3 (MIB-2), ONVIF Protocol Security HTTPS (TLS), IP filtering, 802.1x, digest authentication (ID/PW) ONVIF conformance OS: Windows®, Mac® OS, Linux® Web viewer Browser: IE*, Google Chrome*, Mozilla Firefox*, Safari* NOTE: Chrome browser is recommended for IVA configuration Video management software DW Spectrum® IPVMS ENVIRONMENTAL -4°F ~ 122°F (-20°C ~ 50°C) Operating temperature 10-90% (non-condensing) Operating humidity IP rating IP67-rated IK rating IK10 impact-resistant Other certifications UL listed, CE, FCC, RoHS ELECTRICAL DC 12V, PoE IEEE 802,3af Class3, (Adapter not included) Power requirement DC12V: max 6.5W PoE: max 7.8W Power consumption MECHANICAL Aluminum vandal ball housing Material 4.92" x 4.8" (125 x 122 mm) Dimensions 1.76 lbs (0.8 kg) Weight Warranty 5 year warranty







